ASSEMBLY INSTRUCTIONS






TO assemble safety cables: 1. Join fixture safety cables with safety cable from ceiling.

cable lock nut.

lock nut, secure screws with screwdriver.







Barrett Large Knurled Linear Chandelier

Item # RI 5226

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING***SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND **INSTALLATION ARE FINAL.**

- 1. Carefully remove all parts from the box.
- 2. Thread the tube (K) to the fixture body (L).
- 3. Let the lock collar (I) and canopy (H) pass through the tube (J & K).
- 4. Drill 4 holes on the ceiling and make sure the hole distance will match to the holes on the mounting plate (E) exactly.
- 5. Knock the anchors (D) into the wall holes.
- 6. Attach the mounting plate (E) to the tube (J) and secure with lock washer (C) and nut (B) by using the wrench.
- 7. Attach the mounting plate (E) to the outlet box and secure with mounting screws (G), then secure the screws (F) to the anchors (D).
- 8. Measure the wires and cut. Be certain to leave enough to connect inside of the canopy.
- 9. Connect the fixture ground (bare) wire with the ground wire from the outlet box using wire nut (A). If your house does not have ground wire, then attach this wire to the green grounding screw inside of the outlet box.
 - IT IS IMPERATIVE THAT THIS FIXTURE BE GROUNDED
- 10. Connect the fixture Neutral wire (ribbed, no markings) with the neutral wire from the outlet box using wire nut (A).
- 11. Connect the fixture Hot (smooth edge, markings) wire with the hot wire from the outlet box using wire nut (A).
 - DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
- 12. Tuck these wire connections neatly into the outlet box to secure.

RALPH LAUREN

ASSEMBLY INSTRUCTIONS






1. Join fixture safety cables with safety cable from ceiling.

cable lock nut.

lock nut, secure screws with screwdriver.



Bulb (Not included)



Item # RL 5226

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING***SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND **INSTALLATION ARE FINAL.**

13. Put canopy (H) to the mounting plate (E) and secure with lock collar (I).

- 14. If you have purchased with a metal shade (M), put it on the socket cup.
- 15. Insert bulbs (not included) into the sockets.
- 16. Installation is complete, turn on power at fuse or circuit breaker.

***Clean with a dry, soft cloth only. Use no harsh abrasives or chemical agents.







